

FF TLF 2500

Rescue pumper



Characteristics

- ❖ The Flammifer FF TLF 2500 is a rescue pumper, 10 t GVW, with a crew cab for up to 7 persons.
- ❖ It is intended for fire extinguishing from smaller towns to larger cities and also extinguishing fires in open spaces. Its short wheelbase and its overall length reduces the turning radius and makes it easier to operate the vehicle in a narrow surroundings.
- ❖ The fire engine is equipped with a fire extinguishing pump of normal and high pressure, one high pressure rapid intervention hose reel, high pressure water/foam nozzle and a 2500 litres water tank located in the central part of the fire superstructure



FLAMMIFER



Flammifer d.o.o • Ulica akademika Milana Heraka 22 • 47280 Ozalj • Croatia

Tel.: +385 (0)47/731-048 • +385 (0)47/731-068 • +385 (0)47/ 731-088 • Fax: +385 (0)47/731-008 • GSM: +385 (0)91/6645-631

www.flammifer.com • www.facebook.com/FlammiferOzalj • sales@ flammifer.hr



Basic firefighting equipment

- ❖ 2500 L water tank made of PE-HD
- ❖ normal and high pressure pump type:
 - FPN 10-2000, FPH-40-250
- ❖ High pressure rapid intervention hose reel of 60 or 80 m in length with electrical reeling and high pressure water/foam nozzle
- ❖ Ladders for roof access to superstructure
- ❖ Brackets of firefighting equipment defined by client

Supstructure

- ❖ Complete superstructure is made of light material (aluminium)
- ❖ Three aluminium roller shutters with bar lock on each side of the vehicle
- ❖ On the back side door or roller shutter with a bar lock
- ❖ Internal superstructure LED Lighting is turned on during opening of the superstructure
- ❖ LED lighting of the surroundings, laterally and back
- ❖ Easy removal of firefighting equipment and its large transparency
- ❖ Heavier equipment fitted low and easily accessible



Chassis

Main characteristics of the chassis:

- ❖ Renault Midlum 220.10 DC 4x2 EURO 5
- ❖ Crew cab for 7 persons (1+2+4)
- ❖ Wheelbase: 3200 mm
- ❖ Engine power: 220HP / 161kW
- ❖ Dimensions of the vehicle:
 - LxWxH: 6300x2450x2950 mm
- ❖ GVW: 10.000 kg

Option

- ❖ Light mast with 4 LED reflectors and pneumatic extraction
- ❖ Roof turret: capacity of 1,600 lit./min, mounted on the roof of the superstructure, foldable with manual control of engine's RPM
- ❖ Second HP rapid intervention hose reel with 60 or 80 m of hose
- ❖ NP rapid intervention hose reel with 25 m of hose
- ❖ Rescue winch

Signalization

- ❖ Signalization of the vehicles according to regulations for firefighting vehicles
- ❖ LED Signal light bar on the roof of the vehicle
- ❖ Two LED flashlights on the front and the back of the vehicle
- ❖ Multi-tonal fire siren with PA system
- ❖ Setup for installation of radio
- ❖ All the main signs on the client's language
- ❖ All other signalization according to national regulations



POSSIBILITY OF INSTALLATION OF THE BRACKET AND ARRANGEMENT OF FIREFIGHTING EQUIPMENT ACCORDING TO CLIENT'S REQUIREMENTS.