



## FF TLF 1500/200 4X4 DC

### FIRST RESPONSE VEHICLES



Water tank capacity / foam

1500 l / 200 l

Pump

FPH 40-250

Drive

4x4

Equipment compartments

4 pcs

Engine power

κW 129 /HP 175

GVW

7,5 t

Crew

7 (1+2+4)

Dimensions of the vehicle (mm)

5715 x 2070 x 2750  
LxWxH



**Flammifer d.o.o.**

Ul. akademika Milana Heraka 22

47280 Ozalj, Croatia

Phone: +385 (0)47 731 028, +385 (0)47 731 068

info@flammifer.com

www.facebook.com/FlammiferOzalj



[www.flammifer.com](http://www.flammifer.com)

# FF TLF 1500/200 DC

FIRST RESPONSE VEHICLES **4x4**

## CHASSIS DESCRIPTION

- ▶ Chassis (brand, type): Mitsubishi Fuso Canter 6C18D 4x4
- ▶ Engine power (kW/PH): 129/175
- ▶ Wheelbase (mm): 3415
- ▶ Crew: 7 (1+2+4)
- ▶ GVW (t): 7,5
- ▶ Dimensions of the vehicle LxWxH (mm): 5715 x 2070 x 2750
- ▶ Drive: 4x4

## BASIC FIREFIGHTING EQUIPMENT

- ▶ Water tank capacity/foam (l): 1500/200
- ▶ Internal water tank
- ▶ Water/foam tank material: PEHD
- ▶ Firefighting pump EN 1028, high pressure: FPH 40-250
- ▶ Automatic vacuum device
- ▶ Rapid intervention hose reel with nozzle and electrical reeling
- ▶ High pressure rapid intervention hose reel hose length (m): 60
- ▶ Firefighting equipment brackets
- ▶ Ladders for superstructure roof access

## SIGNALIZATION

- ▶ Regulated firefighting signalization
- ▶ LED signal light bar on the roof of the vehicle
- ▶ LED flashlights on the front and the back of the vehicle (quantity): 2+2
- ▶ Multi-tonal fire siren with PA system
- ▶ Set-up for installation of the radio
- ▶ All main signs in the client's language
- ▶ Visual appearance according to client's request

## SUPSTRUCTURE

- ▶ Superstructure material: Alu
- ▶ Lateral equipment compartments with side door or roller shutter with a bar lock (quantity): 4
- ▶ Rear equipment compartments with side door or roller shutter with a bar lock
- ▶ Automatic internal LED lightning of the compartments
- ▶ LED lighting of the surroundings, laterally and rear
- ▶ Well arranged and easily accessible firefighting equipment
- ▶ Heavier equipment fitted low and easily accessible

## OPTIONS

- ▶ High-pressure module with pump (42l/100 bar) with high pressure hose reel length 60/80/120 m including electrical reeling, powered by petrol engine 10,2 kW, electrical and manual ignition, foam mixing device 1-6% and automatic accelerator
- ▶ Light mast (2 or 4 LED reflectors), pneumatical extraction
- ▶ Front rescue winch
- ▶ Other options according to client's request

